

IN THE ABSTRACT

Please amend the Abstract as follows:

[[The]] A door for an automated machine comprises a door chassis delimiting an opening and equipped with a guide [[means]] for the movement of at least one mobile panel, between a closed position in which the façade of the mobile panel at least partly closes the opening and an open position in which the mobile panel is located laterally with respect to the opening. [[According to the invention, the]] The mobile panel comprises a reception structure for a man-machine interface for which the Interface façade is accessible when the mobile panel is in the closed position, and a reception structure displacement mechanism [[means]] assuring that when the mobile panel is in the open position, the façade of the man-machine interface is positioned [[moved towards the opening]] so that an operator in position in front of the opening can access the opening and the man-machine interface at the same time.

A clean copy of the abstract is attached as the last sheet of this Amendment.

ABSTRACT

A door for an automated machine comprises a door chassis delimiting an opening and equipped with a guide for the movement of at least one mobile panel, between a closed position in which the façade of the mobile panel at least partly closes the opening and an open position in which the mobile panel is located laterally with respect to the opening. The mobile panel comprises a reception structure for a man-machine interface for which the interface façade is accessible when the mobile panel is in the closed position, and a reception structure displacement mechanism assuring that when the mobile panel is in the open position, the façade of the man-machine interface is positioned so that an operator in position in front of the opening can access the opening and the man-machine interface at the same time.